Wall Praise Vinyl Colors

Any Wall Praise can be ordered in the colors shown below. Include the color # and name in your order.

	•
O22 Lemon Yellow Pantone 113 c	O55 Mint Pantone 333 c
O21 Yellow Pantone 1235 c	O54 Turq. Pantone 326 c
O20 Dk Gold Pantone 1375 c	O61 Green Pantone Hexachrome green c
036 Orange Pantone 165 c	063 Lime Pantone 381 c
083 Terra Cotta Pantone 1595 c	060 Pine Pantone 342 c
O47 Orange Red Pantone Warm Red c	O50 Navy Pantone 294 c
O31 Red Pantone 1788 c	O57 Br Blue Pantone 2935 c
O3O Dk Red Pantone 186 c	O61 Baby Bl. Pantone 2955
O40 Violet Pantone 2602 c	082 Beige Pantone 5035 c
O42 Lavender Pantone 2562 c	O81 Mocha Pantone 5005 c
O41 Hot pink Pantone 225 c	080 Choco Brown Pantone 1545 c
O45 Pink Pantone 218 c	O74 Med Grey Pantone 7544 c
O92 Metallic Copper Pantone 1385 c	O73 Dk Grey Pantone 7545
O91 Metallic Gold Pantone 729 c	070 Black
OOO Matallia Cilvan D	O10 White
090 Metallic Silver Pantone 5155 c	O10 White

Technical specs of removable vinyl

Adhesive

Polyacrylate dispersion, removable

Areas of Use

Due to its special release characteristics, it is ideal for use in computer-aided signmaking (CAS) equipment.

For short- and medium-term outdoor applications in display and exhibition stands. Certified according to DIN 4102-B1.

Thickness

(without protective paper and adhesive) 3 mil

Dimensional Stability

(FINAT-TM 14) adhered to steel, no shrinkage in cross direction, in length <.016"

Temperature Resistance

adhered to aluminum, -40°F to +176°F no variation

Adhesive Power

(FINAT-TM 1, after 24 h, stainless steel, average) 1.65 lb/in²

Minimum application temperature

+50°F

Outdoor Durability

(based on vertical surface exposure) 3 years

Removability

residueless removal within 2 years

Description

Soft PVC film that features a matte surface to suppress unwanted reflection and residue-free removal for two years.

Release Paper

78 # custom silicone-coated paper with special release characteristics that provide excellent weeding and release values. Customized blue silicone paper liner for white provides superior contrast for cutting and weeding.

Seawaterability

adhered to aluminum, no variation after 48 h/73°F

Surface finish

matte